

AMENDMENT TO THE CLAIMS

This listing of claims will replace all prior versions and listings of claims in the application:

LISTING OF CLAIMS

Claim 1 (currently amended): A tool suspension device, comprising:

a main body having a first side formed with a mounting hole and a second side provided with a mounting portion;

the mounting hole of the main body ~~has~~ having a periphery formed with a catch edge; ~~and~~

the mounting portion of the main body ~~has~~ having an inside formed with a mounting space communicating with the mounting hole; and

a retaining member mounted on an end face of the mounting portion of the main body and extended into the mounting space of the mounting portion of the main body, wherein the retaining member is a screw.

Claim 2 (original): The tool suspension device in accordance with claim 1, wherein the mounting portion protrudes outward from the second side of the main body.

Claim 3 (original): The tool suspension device in accordance with claim 1, wherein the mounting space is directed in an axial direction of the mounting portion of the main body.

Claim 4 (canceled)

Claim 5 (canceled)

Claim 6 (currently amended): ~~The tool suspension device in accordance with claim 1, further comprising~~ A tool suspension device, comprising:

a main body having a first side formed with a mounting hole and a second side provided with a mounting portion;

the mounting hole of the main body having a periphery formed with a catch edge;

the mounting portion of the main body having an inside formed with a mounting space communicating with the mounting hole; and

a ratchet wrench mounted on the main body and including a distal end provided with an operation stud mounted in the mounting hole of the main body, and a positioning ball protruded outward from a side wall of the operation stud and rested on the catch edge of the mounting hole of the main body.

Claim 7 (original): The tool suspension device in accordance with claim 6, wherein the ratchet wrench further includes a press member movably mounted in the operation stud and having a first end formed with a enlarged head and a second end formed with a receiving recess to receive the positioning ball, and an elastic member urged between the operation stud and the enlarged head of the press member.

Claim 8 (original): The tool suspension device in accordance with claim 7, further comprising a retaining member mounted on an end face of the mounting portion of the main body and extended into the mounting space of the mounting portion of the main body, wherein the retaining member is rested on the second end of the press member to retain the press member, thereby forming a locking state by

engagement of the retaining member with the press member, so that the press member cannot be pressed and moved, and the positioning ball will not detach from the catch edge of the mounting hole of the main body.

Claim 9 (original): The tool suspension device in accordance with claim 6, wherein the operation stud is inserted through the mounting hole of the main body into the mounting space of the mounting portion of the main body.